



Product Description

High quality acrylic, multiadhesive enamel and special acrylic resins and highly colour fast pigments based decoration.



Technical Characteristics

Colour	White
Appearance	Satin
Touch-dry	30-60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 6 hours
Yield	10 - 13 m ² /l, coat, depending on conditions of surface
Thinner	Water
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

Properties

Very good adhesion on different surfaces: Steel, iron, galvanised, copper, brass, aluminium, ceramics, PVC, rigid, formica, methacrylate, wood, cork, etc. Applies directly on steel, no primer needed. Other surfaces: contact us.

Antioxidant properties

Easy to apply

Excellent levelling

Resistant to the outdoors

Half aqueous composition

Environmentally friendly

Odourless

Non-drip

Excellent whiteness

Non-yellowing

Filling power

Good covering power.

Finish hard-wearing, adherent, fine and soft

Resistant to rubbing, wear and washing

Applications

Suitable for protection and decoration de on indoor and outdoor surfaces, windows, doors, handrails, fences, balconies, railings, radiators and tiles, etc..

Method of Use

Stir the contents of the pot well

Apply in thin, even, well-spread coats

Application at: Round brush, roller and spray gun

Preparation of surfaces

On unpainted surfaces: Sandpaper, clean and eliminate dust, grease, oil, rust, waxes, minor faults, etc...

Apply the following preparations:

On wood and plaster apply TAPAPOROS AL AGUA ECOBARP o IMPRIMACION SELLADORA BLANCO

Apply: 2 ó 3 coats with drying time between applications

On with old paintwork surfaces: Remove damaged paintwork and proceed as for unpainted surfaces

Recommendations before application

Do not apply in temperatures below 10°C.

Should not be used in bright sunlight or when the object being painted is at a high temperature

Direct application on: Iron, galvanised, aluminium, etc.

Other data

Packaging 0.750L, 4L

Remarks

Shake contents of containers before use.

For toxicological standards, consult FICHA DE SEGURIDAD.

Do not store opened or started containers.

Apply with good air renewal.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 05-04-2016 This sheet replaces all previous versions.