



New Guard Coatings Group

A global reputation to protect.

You have acquired this data sheet from the New Guard Coatings Group.

All information listed is correct at the time of print.

www.newguardcoatings.com

NORTH • SOUTH EAST • MIDLANDS • NORTH WEST • HULL • SCOTLAND

ESMALTE ANTIOXIDANTE



Product Description

High quality antioxidant enamel and alkyd resin with special characteristics and highly colour fast pigments based decoration.

Certificates

Clasificación categoría i) de Esmaltes decorativos anticorrosivos de altas prestaciones en base disolvente, según norma UNE 48613:2014 y UNE 48316:2014/1M:2015

Carta de Colores

[Carta de colores Esmaltes Antioxidantes](#)



Technical Characteristics

Colour	White, black and colours as per chart
Appearance	Gloss
Touch-dry	4 - 5 hours, depending on thickness applied and ambient conditions
Repainting	After 24 hours
Yield	11 - 13 m ² /l, coat, depending on conditions of surface
Thinner	DILUYENTE SINTETICOS Y GRASOS 250
Storage	Excellent up to 1 year in original container, under normal temperature and humidity conditions.

Properties

- Finish anti-corrosive, glossy, adherent, hard-wearing and fine
- Easy to apply
- Excellent levelling
- Non-drip
- Filling power
- Good covering power.
- Resistant to the outdoors even extreme weather conditions
- Resistant to rubbing, wear and washing
- Unchangeable colours

Applications

Suitable for decorate and protect indoor and outdoor surfaces such as: Doors, handrails, fences, balconies, railings, windows, farm machinery, radiators, public works and industrial facilities, etc... Covers all the needs of the professional and the housewife

Method of Use

- Stir the contents of the pot well
- Apply in thin, even, well-spread coats
- A round brush and roller: as it comes in the pot or thinned with DILUYENTE SINTETICOS Y GRASOS 250
- A aerographic spray and airless: adjust viscosity with DILUYENTE SINTETICOS Y GRASOS 250

Preparation of surfaces

- On unpainted surfaces: Sandpaper, clean and eliminate dust, grease, oil, rust, waxes, minor faults, etc...
- Totally remove rust and lamination crusts by sanding, scraping or blasting
- On with old paintwork surfaces: Remove damaged paintwork and proceed as for unpainted surfaces
- On iron and steel surfaces: Apply 2 or 3 coats of the same product, dilute the first coat slightly using synthetic and grease solvent allowing the repainting time between coats
- On wood and plaster apply IMPRIMACION SELLADORA BLANCO
- On galvanised and light metals apply IMPRIMACION MULTI-ADHERENTE BLANCO

Apply then at least two coats of the product and leaving repainting time between coats

Other data

Packaging	0.375L, 0.75L and 4L
VOCS GR/L	405

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 18-07-2017 This sheet replaces all previous versions.