

New Guard Coatings Group

A global reputation to protect.

You have acquired this data sheet from the New Guard Coatings Group.

All information listed is correct at the time of print.



uksales@newguardcoatings.com



+44 1937 586311

Global Head Office: New Guard Coatings Ltd, Sandbeck Way, Wetherby, Leeds, LS22 7DN





SAFETY DATA SHEET

GUARD SOLVENT F

Page: 1

Compilation date: 20/04/2009

Revision date: 19/03/2015

Revision No: 1

Reference: A0055B

Sent to: Public Server Addition.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GUARD SOLVENT F

REACH registered number(s): 01-2119458049-33

CAS number: 64742-82-1

Synonyms: HYDROCARBONS,C9-C12,N-ALKANES,AROMATICS(2-25%)
WS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Manufacture of substance. Distribution of substance. Formulation & (re)packing of substances and mixtures. Uses in coatings. Use in cleaning agents. Lubricant / Lubricating oil. Use as a fuel. Use in metal working fluids / Rolling oils. Agrochemical uses. Use as a functional fluid. Laboratories. Road and construction applications. This product is not recommended for any industrial, professional or consumer use other than the identified Uses above.

1.3. Details of the supplier of the safety data sheet

Global Head Office: New Guard Coatings Group
Sandbeck Way
Wetherby
West Yorks
LS22 7DN
United Kingdom



Tel: 01937 586311

Email: uksales@newguardcoatings.com

www.newguardcoatings.com

1.4. Emergency telephone number

Emergency tel: 01423 358058 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Xn: R65; Xn: R48/20; -: R66; -: R67; N: R51/53

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT RE 1: H372; -: EUH066

Most important adverse effects: Flammable. Harmful: may cause lung damage if swallowed. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Repeated exposure may

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 2

cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H336: May cause drowsiness or dizziness.
H372: Causes damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.
EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS07: Exclamation mark
GHS02: Flame
GHS09: Environmental
GHS08: Health hazard



Precautionary statements: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P273: Avoid release to the environment.

Label elements under CHIP:

Hazard symbols: Harmful.
Dangerous for the environment.



Risk phrases: R10: Flammable.
R65: Harmful: may cause lung damage if swallowed.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S23: Do not breathe vapour.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 3

S24: Avoid contact with skin.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

CAS number: 64742-82-1

REACH registered number(s): 01-2119458049-33

Contains: Substance contains less than 0.1%w/w benzene.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Seek medical advice if soreness or redness persist.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues

Ingestion: NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Drink plenty of water. If vomiting occurs, keep head low. Get medical attention immediately.

Inhalation: Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice. If breathing stops or shows signs of failing, give artificial respiration. Get medical advice if the symptoms continue.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No specific health warnings noted.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 4

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Foam, Dry Powder, Co2, Halon, fine water spray suitable. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid spilling. Avoid contact with skin and eyes. Avoid direct contact with the substance. Avoid all sources of ignition. Take precautionary measures against static discharges. Ensure all equipment is properly earthed. Avoid inhaling vapour

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Original container stored in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	350mg/m3(The mix)	-	-	-

DNEL/PNEC Values

WHITE SPIRIT

Type	Exposure	Value	Population	Effect
DNEL	Dermal	44mg/kg	Workers	Systemic
DNEL	Inhalation	330mg/m3	Workers	-
DNEL	Dermal	26 mg/kg	Consumers	Systemic
DNEL	Inhalation	71 mg/m3	Consumers	Systemic
DNEL	Oral	26 mg/kg	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Unlikely to be necessary where adequate ventilation is provided.

Hand protection: Ensure gloves are manufactured/tested in accordance with BS EN 374. Nitrile gloves. PVA gloves. Neoprene gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Hydrocarbon

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: 0.012cm²/s

Boiling point/range°C: 135-200

Melting point/range°C: <-20

Flammability limits %: lower: 0.6

upper: 7.2

Flash point°C: 38

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >200

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 6

Relative density: 0.750

VOC g/l: No data available.

Vapour pressure: 0.23 kPa@20c

pH: No data available.

9.2. Other information

Other information: Surface tension : 0.02 mN/m (25 C)

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
VAPOURS	RAT	4H LC50	>13.1	mg/l
DERMAL	RBT	LD50	>3400	mg/kg
ORAL	RAT	LD50	>15000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Based on test data
STOT-repeated exposure	-	Based on test data
Aspiration hazard	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 7

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No specific health warnings noted.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
Daphnia magna	48H EC50	10-20	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: As for substance. Used containers must not be cut up or punctured until completely purged of product residues.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1300

14.2. UN proper shipping name

Shipping name: TURPENTINE SUBSTITUTE

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 8

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT F

Page: 9

Legend to abbreviations: PNEC = predicted no effect level
DNEL = derived no effect level
LD50 = median lethal dose
LC50 = median lethal concentration
EC50 = median effective concentration
IC50 = median inhibitory concentration
dw = dry weight
bw = body weight
cc = closed cup
oc = open cup
MUS = mouse
GPG = guinea pig
RBT = rabbit
HAM = hamster
HMN = human
MAM = mammal
PGN = pigeon
IVN = intravenous
SCU = subcutaneous
SKN = skin
DRM = dermal
OCC = ocular/corneal
PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.