



New Guard Coatings Group

- A global reputation to protect.

The information herewith is given with the best of New Guard Coatings Group knowledge.

Rights are reserved to change and update the data without notice.

This information is not exhaustive and it is the user's responsibility to ensure that this data sheet is the most current by contacting their local New Guard Coatings Group branch prior to using the coating/product.

www.newguardcoatings.com

NORTH • SOUTH EAST • MIDLANDS • NORTH WEST • HULL • SCOTLAND



SAFETY DATA SHEET

GUARD SOLVENT B

Page: 1

Compilation date: 15/04/2009

Revision date: 14/12/2011

Revision No: 1

Reference: A0051B

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GUARD SOLVENT B

Product code: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Global Head Office: New Guard Coatings Group
Sandbeck Way
Wetherby
West Yorks
LS22 7DN
United Kingdom



Tel: 01937 586311

Email: uksales@newguardcoatings.com

www.newguardcoatings.com

1.4. Emergency telephone number

Emergency tel: 01423 358058 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21/22; Xi: R36/38; Xn: R48/20; N: R51/53; Xn: R63; Xn: R65; Xn: R68/20/21/22

Classification under CLP: Eye Irrit. 2: H319; STOT RE 2: H373; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Repr. 2: H361f; Skin Irrit. 2: H315; STOT SE 3: H336

Most important adverse effects: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 2

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



Precautionary statements: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.
P273: Avoid release to the environment.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.

Dangerous for the environment.



Risk phrases: R11: Highly flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 3

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE - REACH registered number(s): 01-2119471310-51

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|----------|---|--|---------|
| 203-625-9 | 108-88-3 | F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67 | Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336 | 10-30% |

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46

| | | | | |
|-----------|----------|---------------------------------|--|--------|
| 205-500-4 | 141-78-6 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 10-30% |
|-----------|----------|---------------------------------|--|--------|

XYLENE - REACH registered number(s): 01-2119488216-32

| | | | | |
|-----------|-----------|-----------------------------|---|-------|
| 215-535-7 | 1330-20-7 | -: R10; Xn: R20/21; Xi: R38 | Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315 | 1-10% |
|-----------|-----------|-----------------------------|---|-------|

N-HEXANE

| | | | | |
|-----------|----------|--|---|-------|
| 203-777-6 | 110-54-3 | F: R11; Xi: R38; Xn: R48/20; Xn: R62; Xn: R65; -: R67; N: R51/53 | Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411 | 1-10% |
|-----------|----------|--|---|-------|

ETHANOL - REACH registered number(s): 01-2119475610-43

| | | | | |
|-----------|---------|--|--------------------|-------|
| 200-578-6 | 64-17-5 | F: R11 Substance with a Community workplace exposure limit. | Flam. Liq. 2: H225 | 1-10% |
|-----------|---------|--|--------------------|-------|

ETHYL METHYL KETONE

| | | | | |
|-----------|---------|---------------------------------|--|-------|
| 201-159-0 | 78-93-3 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|---------|---------------------------------|--|-------|

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 4

ACETONE - REACH registered number(s): 01-2119471330-49

| | | | | |
|-----------|---------|---------------------------------|---|-------|
| 200-662-2 | 67-64-1 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|---------|---------------------------------|---|-------|

N-BUTYL ACETATE - REACH registered number(s): 01-2119485493-29

| | | | | |
|-----------|----------|---|---|-------|
| 204-658-1 | 123-86-4 | -: R10; -: R66; -: R67 Substance with a Community workplace exposure limit. | Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|----------|---|---|-------|

LOW BOILING POINT NAPHTHA - UNSPECIFIED - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED LIGHT,
DEAROMATIZE

| | | | | |
|-----------|------------|---|---|-------|
| 295-434-2 | 92045-53-9 | Xn: R65; F+: R12; Xi: R38; N: R51/53 | Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411 | 1-10% |
|-----------|------------|---|---|-------|

PROPAN-2-OL

| | | | | |
|-----------|---------|-------------------------|--|-------|
| 200-661-7 | 67-63-0 | F: R11; Xi: R36; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336 | 1-10% |
|-----------|---------|-------------------------|--|-------|

ISOPROPYL ACETATE

| | | | | |
|-----------|----------|---------------------------------|---|-------|
| 203-561-1 | 108-21-4 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|----------|---------------------------------|---|-------|

METHYL ACETATE

| | | | | |
|-----------|---------|---------------------------------|---|-------|
| 201-185-2 | 79-20-9 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|---------|---------------------------------|---|-------|

METHANOL - REACH registered number(s): 01-2119433307-44

| | | | | |
|-----------|---------|--|---|-------|
| 200-659-6 | 67-56-1 | F: R11; T: R23/24/25; T: R39/23/24/25 | Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370 | 1-10% |
|-----------|---------|--|---|-------|

ISOBUTANOL - REACH registered number(s): 01-2119484609-23

| | | | | |
|-----------|---------|-------------------------------------|--|-------|
| 201-148-0 | 78-83-1 | -: R10; Xi: R37/38; Xi: R41; -: R67 | Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336 | 1-10% |
|-----------|---------|-------------------------------------|--|-------|

4-METHYLPENTAN-2-ONE

| | | | | |
|-----------|----------|-------------------------------------|--|-------|
| 203-550-1 | 108-10-1 | F: R11; Xn: R20; Xi: R36/37; -: R66 | Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066 | 1-10% |
|-----------|----------|-------------------------------------|--|-------|

PROPYL ACETATE

| | | | | |
|-----------|----------|---------------------------------|---|-------|
| 203-686-1 | 109-60-4 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|----------|---------------------------------|---|-------|

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 5

BUTAN-1-OL

| | | | | |
|-----------|---------|--|---|-----|
| 200-751-6 | 71-36-3 | -: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67 | Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336 | <1% |
|-----------|---------|--|---|-----|

PROPAN-1-OL

| | | | | |
|-----------|---------|-------------------------|---|-----|
| 200-746-9 | 71-23-8 | F: R11; Xi: R41; -: R67 | Flam. Liq. 2: H225; Eye Dam. 1: H318; STOT SE 3: H336 | <1% |
|-----------|---------|-------------------------|---|-----|

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues
- Ingestion:** Wash out mouth with water. If patient is conscious, give water to drink. If patient feels unwell, seek medical advice. DO NOT INDUCE VOMITING.
- Inhalation:** Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.
- Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 6

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Original container stored in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 7

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 616 mg/m3 | 770 mg/m3 | - | - |

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 191 mg/m3 | 384 mg/m3 | - | - |

ETHYL ACETATE

| | | | | |
|----|---------|---------|---|---|
| UK | 200 ppm | 400 ppm | - | - |
|----|---------|---------|---|---|

XYLENE

| | | | | |
|----|-----------|-----------|---|---|
| UK | 220 mg/m3 | 441 mg/m3 | - | - |
|----|-----------|-----------|---|---|

N-HEXANE

| | | | | |
|----|----------|---------|---|---|
| UK | 72 mg/m3 | No List | - | - |
|----|----------|---------|---|---|

ETHANOL

| | | | | |
|----|------------|---|---|---|
| UK | 1920 mg/m3 | - | - | - |
|----|------------|---|---|---|

ETHYL METHYL KETONE

| | | | | |
|----|-----------|-----------|---|---|
| UK | 600 mg/m3 | 899 mg/m3 | - | - |
|----|-----------|-----------|---|---|

ACETONE

| | | | | |
|----|------------|------------|---|---|
| UK | 1210 mg/m3 | 3620 mg/m3 | - | - |
|----|------------|------------|---|---|

N-BUTYL ACETATE

| | | | | |
|----|-----|-----|---|---|
| UK | 724 | 966 | - | - |
|----|-----|-----|---|---|

PROPAN-2-OL

| | | | | |
|----|-----------|------------|---|---|
| UK | 999 mg/m3 | 1250 mg/m3 | - | - |
|----|-----------|------------|---|---|

ISOPROPYL ACETATE

| | | | | |
|----|--------|-----------|---|---|
| UK | no std | 849 mg/m3 | - | - |
|----|--------|-----------|---|---|

METHYL ACETATE

| | | | | |
|----|-----------|-----------|---|---|
| UK | 616 mg/m3 | 770 mg/m3 | - | - |
|----|-----------|-----------|---|---|

METHANOL

| | | | | |
|----|-----------|-----------|---|---|
| UK | 266 mg/m3 | 333 mg/m3 | - | - |
|----|-----------|-----------|---|---|

ISOBUTANOL

| | | | | |
|----|-----------|-----------|---|---|
| UK | 154 mg/m3 | 231 mg/m3 | - | - |
|----|-----------|-----------|---|---|

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 8

4-METHYLPENTAN-2-ONE

| | | | | |
|----|-----------|-----------|---|---|
| UK | 208 mg/m3 | 416 mg/m3 | - | - |
|----|-----------|-----------|---|---|

PROPYL ACETATE

| | | | | |
|----|-----------|------------|---|---|
| UK | 849 mg/m3 | 1060 mg/m3 | - | - |
|----|-----------|------------|---|---|

BUTAN-1-OL

| | | | | |
|----|---|-----------|---|---|
| UK | - | 154 mg/m3 | - | - |
|----|---|-----------|---|---|

PROPAN-1-OL

| | | | | |
|----|-----------|-----------|---|---|
| UK | 500 mg/m3 | 625 mg/m3 | - | - |
|----|-----------|-----------|---|---|

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves, change regularly to avoid permeation problems. Ensure gloves are manufactured/tested in accordance with BS EN 374.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Perceptible odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Slightly soluble

Also soluble in: Most organic solvents.

Boiling point/range°C: 55-155

upper: 12.8

Autoflammability°C: >203

pH: 7.71

Flammability limits %: lower: 1.1

Flash point°C: <21

Relative density: 0.831-0.881

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 9

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

| Effect | Route | Basis |
|--------------------------|-------------|-----------------------|
| Acute toxicity (harmful) | INH DRM ING | Hazardous: calculated |
| Irritation | OPT DRM | Hazardous: calculated |
| Repeated dose toxicity | INH | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 10

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 11

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361d: Suspected of damaging the unborn child.

H361f: Suspected of damaging fertility.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R12: Extremely flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

[cont...]

SAFETY DATA SHEET

GUARD SOLVENT B

Page: 12

R22: Harmful if swallowed.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R36/37: Irritating to eyes and respiratory system.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R37/38: Irritating to respiratory system and skin.

R38: Irritating to skin.

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R41: Risk of serious damage to eyes.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

