

The information herewith is given with the best of New Guard Coatings Group knowledge.

Rights are reserved to change and update the data without notice.

This information is not exhaustive and it is the user's responsibility to ensure that this data sheet is the most current by contacting their local New Guard Coatings Group branch prior to using the coating/product.

# www.newguardcoatings.com

NORTH • SOUTH EAST • MIDLANDS • NORTH WEST • HULL • SCOTLAND



GUARD SOLVENT G

Page: 1

Compilation date: 16/09/2009 Revision date: 02/02/2012 Revision No: 1 Reference: A0056B

Section 1: Identification of th	ne substance/mixture and of the company/undertaking		
1.1. Product identifier			
Product name:	GUARD SOLVENT G		
REACH registered number(s):			
CAS number:			
EINECS number:	200-662-2		
Synonyms:	PROPANONE		
	of the substance or mixture and uses advised against		
Use of substance / mixture:	bstance / mixture: Manufacture of substance. Distribution of substance. Uses in coatings. Laboratories.		
	use of release agents and binders. Rubber Production and processing. Polymer		
	Processing. Use in cleaning agents. Use in oil and gas field drilling and production		
	operations. Mining chemicals. Blowing Agents This product is not recommended for any		
	industrial, professional or consumer use other than the identified Uses above.		
1.3. Details of the supplier of	f the safety data sheet		
Global Head Office:	fice: New Guard Coatings		
	Sandbeck Way		
	Wetherby		
	West Yorkshire		
	LS22 7DN		
Tel:	+44(0)1937 586311		
Fax:	+44(0)1937 580041		
Email:	uksales@newguardcoatings.com		
1.4. Emergency telephone nu	Imber		
Emergency tel:	01423 358058 (Office Hours Only)		
Section 2: Hazards identifica	tion		
2.1. Classification of the sub	stance or mixture		
	F: R11; Xi: R36; -: R66; -: R67		
Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 2: H225; -: EUH066			
lost important adverse effects: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or			

cracking. Vapours may cause drowsiness and dizziness.



GUARD SOLVENT G

Page: 2

2.2. Label elements			
Label elements under CLP:			
Hazard statements:	H225: Highly flammable liquid and vapour.		
	H319: Causes serious eye irritation.		
	H336: May cause drowsiness or dizziness.		
	UH066: Repeated exposure may cause skin dryness or cracking.		
Signal words:	Danger		
Hazard pictograms:	GHS02: Flame		
	GHS07: Exclamation mark		
Precautionary statements:	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	P280: Wear protective gloves/protective clothing/eye protection/face protection.		
	P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.		
	Rinse skin with water/shower.		
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove		
	contact lenses, if present and easy to do. Continue rinsing.		
	P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position		
	comfortable for breathing.		
	P501: Dispose of contents/container to in accordance with local/regional/national		
	regulations.		
Label elements under CHIP:	:		
Hazard symbols:	Is: Highly flammable.		
	Irritant.		
Risk phrases:	R11: Highly flammable.		
	R36: Irritating to eyes.		
	R66: Repeated exposure may cause skin dryness or cracking.		
	R67: Vapours may cause drowsiness and dizziness.		
Safety phrases:	es: S9: Keep container in a well-ventilated place.		
	S16: Keep away from sources of ignition - No smoking.		
	S25: Avoid contact with eyes.		
	S26: In case of contact with eyes, rinse immediately with plenty of water and seek		
	medical advice.		
	S37: Wear suitable gloves.		
	CO2. Take an action and a construct static discharges		

S33: Take precautionary measures against static discharges.



GUARD SOLVENT G

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This substance is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

#### 3.1. Substances

Chemical identity: ACETONE

### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact:	Remove affected person from from source of contamination. Drench the skin with plenty
	of water. Remove contaminated clothing and wash before reuse. If large areas of the
	skin are affected or if irritation persists, seek medical advice. Continue washing skin for
	at least 20 minutes.
Eye contact:	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye
	open. Remove any contact lenses and open eyes wide apart. Get medical attention if
	any discomfort continues
Ingestion:	Rinse mouth thoroughly. Get medical attention immediately. Keep warm and at rest.lf
	their is difficulty in breathing give oxygen. If breathing stops or shows signs of
	failing,apply artificial respiration.
Inhalation:	Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid
	or complete, seek medical advice.
2. Most important symptom	s and effects, both acute and delayed
Skin contact:	There may be irritation and redness at the site of contact.
-	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

4.2

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. DO NOT USE WATER JETS.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits oxides of carbon. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.



GUARD SOLVENT G

5.0 Ashing for firships	
5.3. Advice for fire-fighters	
Advice for fire-fighters:	In case of fire, wear self contained breathing apparatus. Water may be ineffective but use
	to keep fire-exposed containers cool. Keep run -off water out of sewers and water
	sources. Use water to keep fire exposed containers cool and disperse vapours. Avoid
	water in straight hose stream, will scatter and spread fire.
Section 6: Accidental release	emeasures
6.1. Personal precautions, pr	otective equipment and emergency procedures
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the
	contaminated area with signs and prevent access to unauthorised personnel. Turn
	leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of
	ignition.
6.2. Environmental precautio	
	15
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
6.3. Methods and material for	r containment and cleaning up
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for
	disposal by an appropriate method. Do not use equipment in clean-up procedure which
	may produce sparks.
6.4. Reference to other section	
Section 7: Handling and stor	age
7.1. Precautions for safe han	dlina
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
	Do not handle in a confined space. Avoid the formation or spread of mists in the air.
	Smoking is forbidden. Use non-sparking tools.
7.2. Conditions for safe stora	age, including any incompatibilities
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed. Keep away from
-	sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
	Ensure lighting and electrical equipment are not a source of ignition.
Suitable packaging:	
7.3. Specific end use(s)	
r.o. opecinic enu use(s)	
Section 8: Exposure controls	s/personal protection

8.1. Control parameters



# GUARD SOLVENT G

#### Page: 5

Workplace exposure limits:			Respirable dust		
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	UK	1210 mg/m3	3620 mg/m3	-	-

#### 8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. Ensure lighting and electrical<br/>equipment are not a source of ignition.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:butyl rubber gloves. Use gloves with long sleeves.Eye protection:If risk of splashing,wear safety goggles or face sheild. Eyewash bottle with clean water.Skin protection:Solvent resistant protective clothing.

Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Colourless		
Odour:	Pungent		
Evaporation rate:	Moderate		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Highly soluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Non-viscous		
Boiling point/range°C:	56-58	Melting point/range°C:	-95
Flammability limits %: lower:	2.60	upper:	13.0
Flash point°C:	-18	Part.coeff. n-octanol/water:	0.24@20°C
Autoflammability°C:	465	Vapour pressure:	24.70kPa@20C
Relative density:	0.793	pH:	5-6

9.2. Other information

Other information: Not applicable.

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Reacts in presence of bases.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: No hazardous reactions known.



# GUARD SOLVENT G

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Static discharge.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits Oxides of Carbon.

#### Section 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Based on test data
STOT-single exposure	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

# Section 12: Ecological information

#### 12.1. Toxicity

Ecotoxicity values: Not applicable.

#### 12.2. Persistence and degradability

Persistence and degradability: Product is not expected to bioaccumulate. The product is readily biodegradable in

aerobic systems, using either salt water or fresh water innocula.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This substance is not identified as a PBT substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.



# GUARD SOLVENT G

#### Section 13: Disposal considerations

13.1. Waste treatment methods		
Disposal operations:	Incinerate in suitable combustion chamber. It is the responsibility of the waste generator	
	to determine the Toxicity and physical properties of the material generated to determine	
	the proper waste classification and disposal methods in compliance with applicable	
	regulations.	
Recovery operations:	Use principally as a fuel or other means to generate energy.	
Waste code number:	07 01 04	
NB:	The user's attention is drawn to the possible existence of regional or national	
	regulations regarding disposal.	

# Section 14: Transport information

14.1. UN number

UN number: UN1090

#### 14.2. UN proper shipping name

Shipping name: ACETONE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Marine pollutant: No

# **Section 16: Other information**

Other information

Other information: Since emptied containers retain product residue,follow label warnings even after container is emptied.residual vapours may explode on ignition,do not cut,drill ,grind or weld on or near this container.



# GUARD SOLVENT G

Phrases used in s.2 and 3:EUH066: Repeated exposure may cause skin dryness or cracking.<br/>H225: Highly flammable liquid and vapour.<br/>H319: Causes serious eye irritation.<br/>H336: May cause drowsiness or dizziness.<br/>R11: Highly flammable.<br/>R36: Irritating to eyes.<br/>R66: Repeated exposure may cause skin dryness or cracking.<br/>R67: Vapours may cause drowsiness and dizziness.Legal disclaimer:The above information is believed to be correct but does not purport to be all inclusive<br/>and shall be used only as a guide. This company shall not be held liable for any<br/>damage resulting from handling or from contact with the above product.

Page: 8